



CC LUBE®

CLEAN SEMI-SYNTHETIC, FOODGRADE LUBRICANT H-1

CONTAINS NO NUT OR GM CROP ORIGIN RAW MATERIALS

DESCRIPTION

CC LUBE is a state-of-the-art semi-synthetic, multipurpose lubricant that combines an aluminium complex thickener for extreme water resistance with the latest synthetic ingredients and PTFE to create a semi-transparent, long lasting, high quality lubricant with unequalled quality and performance

CC LUBE is a clean, non-staining, non-drying, biodegradable and unsurpassed in reducing friction, extending machine and equipment life and preventing the formation of rust and corrosion over a broad temperature range.

CC LUBE is approved for use in food machinery applications and is NSF rated H-1.

ADVANTAGES

- NSF H-1 Approved
- Non-toxic, nonstaining.
- Clean lubricant
- Does not dry out
- Odourless
- Contains PTFE
- Prevents rust and corrosion
- Biodegradable
- Extremely water resistant
- Reduces friction

APPLICATIONS

CC LUBE is an excellent clean, multi-purpose lubricant that is safe on nearly all materials, including metal, plastic, rubber, vinyl and wood. It can be used in automotive, electrical, food processing, industrial, marine and residential applications, including:

Bearings Chains Fishing Tackle

Bushings	Conveyors	Gears
Cables	Firearms	Hinges
Industrial Equip.	Linkages	Locks
Machinery	Pulleys	Pumps
Slides	Valves	Winches

PRODUCT CHARACTERISTICS

Service range	-18°C to 204°C (0°F to 400°F)	
Thickener	Aluminium complex	
Fluid type	White oils and Synthetics	
Colour/Appearance	Light straw	
	Semi-opaque	
Dropping Point (ASTM D-566)	260°C (500°F)	
Specific Gravity	0.88	
Additive type	Organic, R&O, PTFE	
Flash Point	>221°C (430°F)	
Autoignition Point (Calculated)	>260°C (500°F)	
NLGI Grade	1 - 1½	
Penetration @25°C (IP50/ASTM D217)	285-315	
Copper Strip Corrosion (ASTM D-4048)	1A	
Shell 4-Ball (ASTM D-2596)		
Weld Point, kgf	126	
Load wear Index	25	
Wear Scar Diameter (ASTM D-2266)	0.7	
Oxidation Resistance (ASTM D-942) PSI Drop, 100Hrs	<5.0	
Base Oil Viscosity (ASTM D-445) cSt @40°C	90-110	

PACKAGING

Code No.	Size	Container
JA70550	30 x 400g	Cartridge
JA70504	12 x 500g	Jar
JA70516	16kg	Metal pail
JA70529	181kg	Barrel

LIMITED WARRANTY

Jet-Lube (UK) Limited makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube (UK) Limited materials and workmanship.

This limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube (UK) Limited.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube (UK) Limited shall not be liable for incidental or consequential damages.

May 2013