



# ROD GREASE

## FOR EXTREME SERVICE

### DESCRIPTION

**ROD GREASE** is a high temperature, Aluminium - based grease suitable for both high and low temperature application .

**ROD GREASE** has a dropping point of 273°C, is highly water resistant and displays excellent work stability under high loads, high speeds, shock and vibration.

The superior lubricating grease base leads to exceptional load carrying and low friction characteristics. It is an all-weather product which lubricates efficiently at temperatures down to -29°C .

**ROD GREASE** has exceptional resistance to the effect of heat, water, weathering, oxidation and heavy loads. it contains rust, corrosion and oxidation inhibitors.

**ROD GREASE** gives unexcelled protection wherever dirt, dust, high humidity, rain and adverse temperatures are critical problems.

### ADVANTAGES

- Aluminium based grease
- Protects rods from wear
- Superior metal adhesion
- Improves coring ability
- Resistant to water, heat, weathering and oxidation
- Excellent work stability

### APPLICATIONS

**ROD GREASE** aids in the prevention of rod chattering and is particularly suited to minimising binding in the hole. The high water resistance allows long life, leading to improved economy. For exceptionally wet or hostile conditions, use **Jet-Lube ROD GREASE EXTRA TACKY**

### PRODUCT CHARACTERISTICS

|   |                |
|---|----------------|
| Thickener   | Aluminium Soap |
| Colour/Appearance                                       | Light beige    |
| Dropping Point (ASTM D-566)                             | 273°C (523°F)  |
| Specific Gravity  | 0.91           |
| NLGI Grade  | 3              |
| Penetration @ 25°C (IP50/ASTM D-217)                    | 238            |
| Copper Strip Corrosion (ASTM D-4048)                    | 1B             |
| Oxidation Resistance (ASTM D942)<br>PSI Drop, 100 hours | <5.0           |
| Base Oil pour point                                     | -29°C (-20°F)  |
| Water washoff resistance, typical                       | <3%            |

### PACKAGING

| Code No. | Size  | Container |
|----------|-------|-----------|
| JA71815  | 16 kg | Pail      |

### LIMITED WARRANTY

Jet-Lube (UK) Limited makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube (UK) Limited materials and workmanship.

This limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube (UK) Limited.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube (UK) Limited shall not be liable for incidental or consequential damages.

Sept 2013